

**Amendments to the Specification:**

Please replace paragraph number [0108] with the following rewritten paragraph:

**[0108]** FIGURES 26 through 29 show in a work environment workstation 4i of a type similar to that shown in FIGURES 19 and 20 configured for a single worker (not shown) according to an exemplary embodiment of the present invention. Workstation 4i includes base panel wall 280, shelving unit 14 providing docking area 38a for containers 8d, 8e, 8f, 8g, 8h, 8i, 8j, and 8k of information display system 6, and mobile table 16. Workstation 4i also includes utility threshold 24 coupled to the top of panel wall 280 on track 30 for sliding movement. As shown in FIGURES 26 and 29, workstation 4i also includes a retractable partition shown as a privacy screen 78 (e.g. of a type similar to a tambour door according to the exemplary embodiment, but of any type of screen material according to various alternative embodiments). Privacy screen 78 is installed within a vertical recess 80 in shelving unit 14 and can selectively be withdrawn from recess 80 (as shown in FIGURES 26 and 29) or retracted into recess 80 (as shown in FIGURES 27 and 28) by a handle 82 (which may include a locking element such as a hook or clasp to retain privacy screen 78 in engagement with a coacting locking element associated with the panel wall or utility threshold or other structure). As shown in FIGURE 26, with containers 8d, 8e, 8f, 8g, 8h, 8i, 8j, and 8k stowed in docking area 38a and utility threshold 24 stowed over docking area 38a, privacy screen 78 can be withdrawn (e.g. drawn across the entry to docking area) to conceal and secure the containers and any articles of furniture within docking area 38a. Workstation 4i is therefore in a secured condition (for example, secured compactly within a 3 feet by 7 feet dimensional footprint). In FIGURE 27, privacy screen 78 (not visible) has been retracted into vertical recess 80 so that the contents of docking area 38a, containers 8d, 8e, 8f, 8g, 8h, 8i, 8j, and 8k and a mobile storage unit 260, are visible. In FIGURE 28, workstation is "open" with fully open container 8k 8f and open container 8j 8g visible and mobile table 16 and mobile storage unit 260 also visible and available for use. In FIGURE 29, utility threshold 24 is deployed (moved along its track) to provide a docking area 38c for a closed container 8g above mobile storage unit 260. Privacy screen 78 is withdrawn toward vertical post 50 of utility threshold 24 to define a floor space section 118m (shown in phantom lines) within which a worker (not shown) can have at least a limited amount of privacy. According to any preferred embodiment, as shown, the retractable partition can be of any material or construction and is configured to provide for security (e.g. in an unoccupied or closed workstation) and privacy (in an occupied workstation).